ΛoFrio



Wellington® ECF 2 AB-2

High performance commercial refrigeration 10-inch (250mm) fan pack

- Universal voltage
- · High efficiency
- Quiet operation
- · Variable speed
- Removable power plug




| Specifications | | | |
|---------------------------|--|--|--|
| Nominal voltage | 100-240V, 50-60Hz | | |
| Speed range | 300-1700 RPM | | |
| Max. input power | 39W | | |
| Max. input current | 0.19A (@230V), 0.35A (@115V) | | |
| Max. Power factor | 0.97 | | |
| EMC protection | 4000V (per EN61000-6-2) | | |
| Insulation class | Class B (130°C) | | |
| Electronic protection | Locked rotor and automatic thermal de-rating | | |
| Refrigerant compatibility | HFC, CO ₂ and hydrocarbon (per IEC 60335-2-89 Annex BB) | | |
| IP rating | IP67 | | |
| Operating temp. range | -30°C to +50°C (-22°F to +122°F) | | |
| Storage temp. range | -40°C to +80°C (-40°F to +176°F) | | |
| Weight | 1.1kg (2.4 lb) | | |
| Approvals | CE CH CH | | |

¹ UL approval pending

Airflow

| Speed | Point | Airflow | | Pressure | | Power |
|-------|-------|---------|-------|----------|--------------------|-------|
| (RPM) | | (m³h) | (cfm) | (Pa) | (H ₂ 0) | (W) |
| 1200 | 1 | 858 | 505 | 0 | 0.00 | 13 |
| | 2 | 552 | 325 | 24 | 0.09 | 14 |
| 1300 | 3 | 936 | 551 | 0 | 0.00 | 16 |
| | 4 | 558 | 328 | 29 | 0.11 | 17 |
| 1550 | 5 | 1117 | 658 | 0 | 0.00 | 27 |
| | 6 | 695 | 410 | 40 | 0.16 | 29 |
| 1700 | 7 | 1231 | 725 | 0 | 0.00 | 36 |
| | 8 | 714 | 420 | 50 | 0.20 | 37 |







Wiring diagram


For single speed operation

For three speed or reversible operation

For variable speed operation







OEM options

Preprogrammed or factory/field programmable speeds


- 3 speed, reversible, or timed-reverse options
- Realtime continuously variable speed control over third mains wire (no extra cables required)
- Custom cable and plug options
- Food Grade rated housing option

Mounting options

Metric:

- 6 x 5 mm holes at 295mm PCD (45°pitch)
- 4 x screw clip slots at 295mm PCD (90° pitch) Imperial:
- 6 x 5mm (0.19") slots allowing for 11.6" to 11.9" PCD (60° pitch)

Dimensions



Trademarks are (as applicable) 'TM' and ® of AoFrio Limited. While all information in this document is believed by AoFrio Limited to be accurate and reliable, AoFrio Limited and its subsidiaries and affiliates and their directors, officers and employees are not responsible for any errors or omissions of any kind whatsoever, and to the maximum extent permitted at law, have no liability in tort, contract, or otherwise to any user and/or any third party.

E: info@aofrio.com

www.aofrio.com