

## SCS 800 Cellular Connected Controller

AoFrio's cellular connected controller delivers an always-on solution with on-site and remote control enabling you to get the most value from the AoFrio IoT ecosystem.



- Real time alerting via always-on cellular connectivity
- Rugged IP54 rated housing
- Advanced refrigeration parameters
- Safety isolated power supply
- Variable speed compressor control
- Variable speed motor control (In development)
- Energy measurement of entire cooler
- Wi-Fi / Cellular geolocation
- 1 month+ backup battery
- Zero voltage relay switching
- Optional external displays<sup>^</sup>
- Accelerometer for motion detection
- High gain internal cellular antenna
- Mounting bracket for easy installation

### Product Models

Model	Reference SKU	Modem options	Outputs	Inputs
SCS 800	SCS-A1-101	LTE Cat M1	8	5
	SCS-A1-201	LTE Cat 1 bis	8	5

### Refrigeration Specifications

<b>Input voltage and current</b>	90-240V AC 50/60 Hz	<b>Refrigerant compatibility</b>	HFC, CO2, Hydrocarbon (per IEC 60335-2-89)
<b>Sensor inputs</b>	5 x Sensor inputs: NTC, PTC, Digital e.g. Door Switch	<b>Ingress protection</b>	IP54
<b>Control outputs</b>	2 x Relay: <ul style="list-style-type: none"> <li>• 1x UL: 7.2FLA &amp; 34.8LRA, IEC: 8A</li> <li>• 1x UL: 3A, IEC: 3A</li> </ul> 2 x 0.4A (solid state triac) 3 x PWM: LED Lighting 1 x VSC control (12V, 25mA)	<b>Operating temperature</b>	IEC -20°C to +55°C (-4°F to +131°F) UL -20°C to +50°C (-4°F to +122°F)
		<b>Storage temperature</b>	-40 °C to +85 °C (-40 °F to 185 °F)
<b>Voltage outputs</b>	1 x 5V DC output for powering displays, gas sensors, PIR etc.	<b>Dimensions</b>	L:155.56mm x W:116.4mm x D:41.1mm
<b>Connectors</b>	Faston + Stocko	<b>Weight</b>	350g (0.77lb)
<b>Rechargeable backup battery</b>	1 month+ BLE and Cellular connectivity	<b>Approvals</b>	*Approvals pending

<sup>^</sup>External display sold separately

## Radio Specifications

<b>Bluetooth</b>	BLE 5.4; 2402–2480 MHz
<b>Wi-Fi</b>	2.4GHz, 802.11 b/g/n; 2412–2462 MHz
<b>Cellular: LTE Cat 1 bis version</b>	LTE-FDD: B1, B2, B3, B4, B5, B7, B8, B12, B13, B18, B19, B20, B25, B26, B28, B66; LTE-TDD: B34, B38, B39, B40, B41; Max output power: 25dBm
<b>Cellular: LTE Cat M1 version</b>	North America (US & Canada): B2, B4, B5, B12, B13, B25, B26; European Union: B1, B3, B8, B20, B28; Max output power: 23dBm
<b>Approvals</b>	FCC ID: 2AHCE-SCS2 IC ID: 21145-SCS2 EU Declaration of Conformity: Please contact AoFrio Limited. info@aofrio.com

## Sensor inputs

<b>AD1 to AD5</b>	Digital 0-5Vdc input, Analog NTC input, PTC Option	Door Switch, Return Air Temp, Evaporator Temp, Condenser Temp, Ambient Temp, PIR
-------------------	---	---

## High voltage outputs

<b>C</b>	Switched 8A output	Compressor power
<b>R</b>	Switched 3A output	Defrost heater / Lights
<b>POut</b>	Non-switched output, 12A max continuous 50A max in-rush, non-repetitive	Current measured power output for cooler components such as heaters, LED lights etc.
<b>S1 &amp; S2</b>	2x 0.4A Triac	Fan on/off control and energy efficient variable speed control


## Low voltage outputs

<b>V_Out</b>	5V DC 200mA output	Power peripherals such as PIRs, tethered display, gas leak sensors
<b>PWM1, PWM2, PWM3 (LED)</b>	0-24Vdc, 1A sink (open drain)	Control dimmable LED lighting
<b>VSC output</b>	12V, 25mA	Frequency control output for VSC speed control.
<b>Display</b>	5V Half duplex serial	UART port for digital LED display

## Refrigeration notes

- Outputs S1 and S2 can be used to switch fan motors and lights or as a signal line to control the speed of Wellington ECR evaporator and condenser fan motors in real time
- R Relay output can be used to switch fans, lights, defrost heater
- PWM outputs are independently controlled
- Pulse Width Modulation outputs providing controls for LED light dimming to provide color tuning or multi-zone intensity control for LED lighting, and PWM2 can be configured to provide frequency-based control for VSCs. LED power supply is not included.
- Total AC current, when combining current on the high voltage outputs, should not exceed 12A.
- Compliance and regulatory approvals pending
- Status LEDs for operational indicators - Power and BLE connectivity
- The POut terminal remains live whenever the SCS 800 is plugged in.

## Dimensions (mm)





## Compliance

---

### United States (FCC)

#### FCC ID: 2AHCE-SCS2

This product contains pre-certified radio modules and complies with Part 15 of the FCC Rules.

#### FCC Compliance Statement

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

1. This device may not cause harmful interference; and
2. This device must accept any interference received, including interference that may cause undesired operation.

#### RF Exposure Statement

1. This equipment complies with FCC radiation exposure limits for an uncontrolled environment.
2. It must be installed and operated with a minimum separation distance of 20 cm between the radiator and any person.

#### Module Identifiers

- Contains FCC ID: **XMR20211108FC41D** (Wi-Fi)
- Contains FCC ID:
  - **XMR202007BG95M6**, SCS-A1-101 LTE Cat M1
  - **XMR2023EG916QGL**, SCS-A1-201 LTE Cat 1 bis

#### Unauthorized Modifications

Changes or modifications not expressly approved by AoFrio could void the user's authority to operate this equipment.

### Canada (ISED)

#### IC ID: 21145-SCS

This device contains licence-exempt transmitters that comply with ISED RSS standards.

#### ISED Compliance Statement

This device contains licence-exempt transmitter(s)/receiver(s) that comply with Innovation, Science and Economic Development Canada's licence-exempt RSS(s).

Operation is subject to the following two conditions:

1. This device may not cause interference; and
2. This device must accept any interference, including interference that may cause undesired operation.

#### RF Exposure Statement (ISED)

This equipment complies with ISED RF exposure limits for an uncontrolled environment.

Maintain **at least 20 cm separation** between the antenna and any person.

#### Module Identifiers

- Contains IC: **10224A-202111FC41D**
- Contains IC:
  - **10224A-2020BG95M6** (SCS-A1-101)
  - **10224A-023EG916QGL**, (SCS-A1-201)

### EU-RED

#### Intended Use

This radio equipment is intended for **commercial refrigeration equipment** and **indoor use** within EU/EEA countries.

#### CE Marking

This product complies with:

- RED 2014/53/EU
- RoHS Directive 2011/65/EU
- WEEE Directive 2012/19/EU

AoFrio Ltd. hereby declares that this equipment is in compliance with the essential requirements and other relevant provisions of Directive 2014/53/EU. Please contact AoFrio Limited for the complete EU Declaration of Conformity. [info@aofrio.com](mailto:info@aofrio.com)



## Radio notes

---

Technologies	Frequency range (MHz)	Max. Transmit power (dBm)
2.4G WLAN	2412-2472MHz	18.50dBm
BLE – Bluetooth (Low Energy)	2402-2480MHz	5.26dBm

## Cellular, LTE M1 variant

Technologies	Frequency range (MHz)	Max. Transmit power (dBm)
LTE FDD Band 1	TX: 1920-1980 RX: 2110-2170	23dBm
LTE FDD Band 3	TX: 1710-1785 RX: 1805-1880	23dBm
LTE FDD Band 8	TX: 880-915 RX:925-960	23dBm
LTE FDD Band 20	TX: 832-862 RX:791-821	23dBm
LTE FDD Band 28	TX: 703-748 RX: 758-803	23dBm

## Cellular, LTE Cat 1 bis variant

Technologies	Frequency range (MHz)	Max. Transmit power (dBm)
LTE FDD Band 1	TX: 1920-1980 RX: 2110-2170	25dBm
LTE FDD Band 3	TX: 1710-1785 RX: 1805-1880	25dBm
LTE FDD Band 5	TX: 824-849 RX: 869-894	25dBm
LTE FDD Band 7	TX: 2500-2570 RX:2620-2690	25dBm
LTE FDD Band 8	TX: 880-915 RX:925-960	25dBm
LTE FDD Band 20	TX: 832-862 RX:791-821	25dBm
LTE FDD Band 28	TX: 703-748 RX: 758-803	25dBm
LTE TDD Band 34	TX: 2010-2025 RX:2010-2025	25dBm
LTE TDD Band 38	TX: 2570-2620 RX: 2570-2620	25dBm
LTE TDD Band 40	TX: 2300-2400 RX: 2300-2400	25dBm
LTE TDD Band 41	TX: 2496-2690 RX: 2496-2690	25dBm

The antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be collocated or operating in conjunction with any other antenna or transmitter.

## EU Importer

---

**Address:** Not applicable

Notes: EU importer and address are not valid at the moment and will be updated in newer versions.